

FREEDOM® RXV®



ELITE LITHIUM POWERTRAIN OR EXI GAS ENGINE WITH CLOSED LOOP EFI

PREMIUM INTERIOR

ADVANCED INTELLIBRAKE™ TECHNOLOGY

FREEDOM® RXV®

IGNITE EVERY ONE OF YOUR SENSES.

Say goodbye to ordinary. The E-Z-GO® Freedom RXV is designed to help you live larger with the choice of an ELITE lithium powertrain activated by Samsung SDI lithium battery technology or the energyefficient EX1 gas engine. You've earned an incredible life, let the Freedom RXV get you there.

KEY FEATURES

- Automotive Style Pedals
- Newly Designed LED Headlights, Taillights & Brake Lights
- 18" Turf Tires
- Horn
- Integrated Storage Basket
- Energy Transfer Bumpers
- Functional Dash with Large Cupholders
- Comfortable Contoured Seats
- Oversized Bagwell
- USB Port
- Optional Rear-Facing Seat Available in RXV 2+2
- Automatic Parking Brake with Advanced IntelliBrake[™] Technology (ELiTE Only)
- State of Charge Meter (ELiTE Only)
- DC/DC Converter (ELiTE Only)
- Fuel Gauge (EX1 Only)
- Optional Alloy Wheels
- Optional Premium Seats





ELITE

EX1

OVERALL LENGTH	94.5 in (240 cm)	
OVERALL WIDTH	47.0 in (119 cm)	
OVERALL HEIGHT (W/O ROOF)	46.5 in (118 cm)	47.5 in (121 cm)
OVERALL HEIGHT (W/ ROOF)	69.5 in (177 cm)	70.0 in (178 cm)
WHEEL BASE	66 in (168 cm)	65.7 in (167 cm)
FRONT WHEEL TRACK	34.5 in (88 cm)	35.5 in (90 cm)
REAR WHEEL TRACK	38.5 in (98 com)	38.0 in (97 cm)
GROUND CLEARANCE @ DIFFERENTIAL	4.0 in (10 cm)	

POWER

DIMENSIONS

POWER SOURCE	56.7-Volt VDC	4-Cycle, 9.15 cu in (150 cc)	
HORSEPOWER (KW)	4.4 hp (3.3 kW) Continuous	11.5 hp (8.6 kW) J1995 Standard	
ELECTRICAL SYSTEM	56-Volt AC	Brushless DC Interal Starter Generator	
BATTERIES (TYPE)	ELITE 2.2, 56.7V Lithium	One, 12-Volt Maintenance-Free	
KEY OR PEDAL START	Pedal		
BATTERY CHARGER	ELiTE Light World Charger 120/230 VAC, 10' DC Cord	N/A	
SPEED CONTROLLER	235-amp Solid-State AC Controller	N/A	
DRIVETRAIN	Motor Shaft Direct Drive	Continuously Variable Transmission (CVT)	
TRANSAXLE	Limited Slip Differential	Differential with Helical Gears	
GEAR SELECTION	Forward-Neutral-Reverse Integrated	Forward-Reverse	
REAR AXLE RATIO	16.99:1	11:47:1 (Forward) 14:35:1 (Reverse)	

PERFORMANCE

SEATING CAPACITY	2 or 4 Passenger		
DRY WEIGHT	615 lb (279 kg)	676 lb (307 kg)	
CURB WEIGHT	662 lb (300 kg)	692 lb (314 kg)	
VEHICLE LOAD CAPACITY	500 lb (227 kg) (2 Passenger) or 800 lb (360kg) (4 Passenger)		
OUTSIDE CLEARANCE CIRCLE	19.2 ft (5.8 m)	19.0 ft (5.8 m)	
SPEED (LEVEL GROUND)	19 mph ± 0.5 mph (30.6 kph ± 0.8 kph)		

STEEDING & SUSDENSION

STEERING & SUSPENSION			
STEERING	Double-Ended Rack and Pinion		
SUSPENSION	Front: Independent A-Arm Coil-Over Shock; Rear: Mono-Leaf Spring With Hydraulic Shocks		
SERVICE BRAKE	Induction Motor	Rear Wheel Mechanical Self-Adjusting Drums	
PARKING BRAKE	Automatic Electro-Magnetic	Self-Compensating, Single Point Engagement	
TIRES	18 x 8.50-8 (4-ply rated)		
BODY & CHASSIS			
FRAME	Welded Steel with Powder-Coat Protection		
BODY & FINISH	Injection Molded TPO		
AVAILABLE BODY COLORS	Almond, Black, Bright White, Burgundy, Forest Green, Inferno Red, Ivory, Metallic Charcoal, Ocean Grey, Patriot Blue, Platinum, Slate		

AVAILABLE SEAT COLORS	
AVAILABLE PREMIUM	
SEAT COLORS	

Stone Beige, Black (custom colors also available) Mushroom, Grey, Black (custom colors also available)







EZGO.com BUILT RIGHT. **RIGHT HERE.**

Features and specifications of vehicles subject to change without notice. Vehicles as photographed may include options not included on base model. ©2022 Textron Specialized Vehicles Inc. 822014-G23 (Rev. 05/2022)